

Technical data sheet

PetroPAN PP-HD

Alkaline high pressure cleaner

Description	PetroPAN PP-HD is an alkaline cleaner for the streak and residue-free cleaning of surfaces. All high-pressure cleaning devices are suitable for this application.
Applications	PP-HD is especially used for exterior and underbody washing of cars, trucks, tank and silo vehicles as well as for cleaning tarpaulins, plastic boats, wash halls, awnings and tiled walls.
Specification	PP-HD is alkaline, contains complexing agents and surfactants.
Processing:	Dilute PP-HD 1:10 to 1:20 with water, depending on the soiling and washing system. Spray the object to be cleaned at low pressure. Leave to work for 5 to 10 minutes, then rinse off with plenty of water, including high-pressure water jets. PP-HD can also be applied diluted with water by sponge, brush or brush.
Disposal	The mixture resulting from cleaning must be disposed of in accordance with the legal regulations.
Hazard- and Precautionary- Statements	H315 Causes skin irritation H318 Causes serious eye damage. P102 Keep out of reach of children. P280 Wear protective gloves / eye protection / face protection P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.

With the publication of this issue, the previous technical data sheets are invalid. Our application technology recommendations are based on our experience to the best of our knowledge and correspond to the current state of knowledge. The information is non-binding and does not constitute a contractual legal transaction. We recommend the user to carry out a test cleaning on the corresponding surfaces in order to be able to take the local conditions into account.